

STEAM LOCOMOTIVE DETAILS

1924 Number	1890 Number	Wheel Arrangement	Weight Metric (<i>Imperial</i>) Tonnes (<i>Tons</i>)	Length Metric (<i>Imperial</i>) Metres (<i>Ft. In.</i>)	Max. Speed kph (<i>mph</i>)	Boiler Pressure Metric (<i>Imperial</i>) kPa (<i>psi</i>)	Tractive Effort Metric (<i>Imperial</i>) kN (<i>lbs</i>)	Driving Wheel Metric (<i>Imperial</i>) mm (<i>Inches</i>)	Cylinder Dia. Metric (<i>Imperial</i>) mm (<i>Inches</i>)	Cylinder Stroke Metric (<i>Imperial</i>) mm (<i>Inches</i>)
CCC 18	E. 18	0-6-0	51.5t (50.5T)	14.5 m (47'6")	40 (25)	827 kPa (120 psi)	83.5 (18770)	1219 (48)	482 (19)	660 (26)
(1004)	M. 78	0-4-2	52.8t (52T)	13.18m (43'3")	32 (20)	861 kPa (125 psi)	46.75 (10510)	1676 (66)	432 (17)	609 (24)
1021	F 1212	0-4-0T	21.388t (21T)	5.795m (19'0")	40 (25)	965 kPa (140 psi)	35.87 (8060)	914 (36)	305 (12)	457 (18)
1033	F.355	2-4-0T	39.256t (38.6T)	8.55m (28'1")	20 (32)	965 kPa (140 psi)	70.32 (15810)	1689 (66.5)	482 (19)	660 (26)
1034	Lo 3	0-4-0 T Crane	30.38t (29.9T)		32 (20)	965 kPa (140 psi)	26.93 (6050)	940 (37)	254 (10)	508 (20)
1064	Lo 39	0-2-2 Grab								
1219	C.145	4-4-0	63.588t (62.6T)	14.69m (48'2")	96 (60)	965 kPa (140 psi)	57.82 (13000)	1702 (67)	457 (18)	609 (24)
1301	CC.79	4-4-2T	55.219t (54.3T)	10.879m (35'9")	80 (50)	965 kPa (140 psi)	57.82 (13000)	1702 (67)	457 (18)	609 (24)
1709	H.381	4-4-0	75.438t (74.25T)	15.492m (50'10")	96 (60)	965 kPa (140 psi)	62.64 (14080)	1702 (67)	457 (18)	660 (26)
1803	R.287	0-6-0-T	37.744t (37.15T)	8.546m (28')	48 (30)	965 kPa (140 psi)	51.38 (11550)	1219 (48)	381 (15)	558 (22)
1905	A.97	0-6-0	60.01t (60.05T)	14.462m (47'5")	40 (25)	1034 kPa (150 psi)	85.58 (19240)	1232 (48.5)	457 (18)	609 (24)
2029	A/E.533	2-6-4T	61.42t (61.4T)	11.609m (38'1")	48 (30)	1034 kPa (150 psi)	85.58 (19240)	1232 (48.5)	457 (18)	609 (24)
2419	B.390	2-6-0	77.728t (76.5T)	15.665m (51'5")	48 (30)	965 kPa (140 psi)	86.53 (19450)	1232 (48.5)	457 (18)	660 (26)
2510	B214	2-6-0	74.731t (73.55T)	14.795m (48'7")	48 (30)	965 kPa (140 psi)	86.53 (19450)	1232 (48.5)	457 (18)	660 (26)
2606	I.22	2-6-2ST	66.968t (65.1T)	11.525m (37'10")	48 (30)	1034 kPa (150 psi)	92.71 (20840)	1232 (48.5)	457 (18)	660 (26)
2705	G.1208	2-6-0	81.64t (80.35T)	16.594m (54'5")	48 (30)	1034 kPa (150 psi)	85.58 (19240)	1232 (48.5)	457 (18)	609 (24)
3001T	S.636	4-6-0	101.26t (99.65T)	17.576m (57'8")	80 (50)	1102 kPa (160 psi)	95.3 (21420)	1397 (55)	482 (19)	609 (24)
3137	S.1065	4-6-4T	73.318t (72.16T)	12.448m (40'10")	80 (50)	1205 kPa (175 psi)	98.1 (22050)	1397 (55)	482 (19)	609 (24)
3203	P.8	4-6-0	111.79t (110T)	18.329m (60'2")	96 (60)	1102 kPa (160 psi)	115.6 (25990)	1524 (60)	533 (21)	660 (26)
3214	P.465	4-6-0	111.79t (110T)	18.329m (60'2")	96 (60)	1102 kPa (160 psi)	115.6 (25990)	1524 (60)	533 (21)	660 (26)
3526	NN.1314	4-6-0	127.68t (125.65T)	19.152m (62'10")	112 (70)	1240 kPa (180 psi)	128.89 (28980)	1765 (69.5)	571 (22.5)	660 (26)
3642	-	4-6-0	162.56t (160T)	20.713m (67'11")	112 (70)	1378 kPa (200 psi)	150.74 (33890)	1752 (69)	584 (23)	660 (26)
3801	-	4-6-2	204.43t (201.2T)	23.282m (76'5")	112 (70)	1688 kPa (245psi)	161.35 (36270)	1752 (69)	246 (21.5)	660 (26)
3820	-	4-6-2	198.31t (195.15T)	23.282m (76'5")	112 (70)	1688 kPa (245psi)	161.35 (36270)	1752 (69)	246 (21.5)	660 (26)
5096	T.356	2-8-0	113.07t (111.25T)	18.383m (60'4")	56 (35)	1102 kPa (160 psi)	128.00 (28780)	1295 (51)	533 (21)	660 (26)
5461	TF.1174	2-8-0	126.34t (124.35T)	18.573m (60'11")	56 (35)	1102 kPa (160 psi)	149.27 (33560)	1295 (51)	533 (21)	660 (26)
5595	K.1447	2-8-0	129.51t (127.45T)	18.561m (60'11")	56 (35)	1102 kPa (160 psi)	149.27 (33560)	1295 (51)	558 (22)	660 (26)
5711	-	4-8-2	231.29t (227.6T)	26.691m (87'6")	64 (40)	1378 kPa (200 psi)	249.1 (56000)	1524 (60)	591 (23.25) x3	711 (28)
5908 o	-	2-8-2	152.71t (150.3T)	26.691m (87'6")	64 (40)	1378 kPa (200 psi)	249.1 (56000)	1524 (60)	533 (21)	711 (28)
5910 c	-	2-8-2	153.42t (151T)	20.561m (67'6")	72 (45)	1378 kPa (200 psi)	155.63 (34990)	1524 (60)	533 (21)	711 (28)
6040	-	4-8-4+4-8-4	267.73t (263.5T)	33.121m (108'8")	64 (40)	1378 kPa (200 psi)	282.42 (63490)	1397 (55)	489 (19.25) x4	660 (26)
Archie	-	0-4-0T	(11.5T)	4.877m (16')	-	1205 kPa (175 psi)	-	610 (24)	178 (7)	305 (12)
Kathleen	-	0-4-0ST	(31.5T)	7.544m (24'9")	-	1034 kPa (150 psi)	56.8 (12865)	991 (39)	368 (14.5)	508 (20)
Alison	-	0-4-0ST	(28T)	(26')	-	1102 kPa (160 psi)	(18990)	1118 (44)	406 (16)	609 (24)
EGC No.1	-	0-4-0T	(27T)	(23'1")	32 (20)	1034 kPa (150 psi)	(8640)	914 (36)	(12.25)	457 (18)
BHP 16	-	0-4-0T	(41T)	(26'6")	48 (30)	1240 kPa (180 psi)	(17950)	1168 (46)	381 (15)	609 (24)
Bronzewing	-	0-6-0ST	(61T)	-	40 (25)	1240 kPa (180 psi)	(24342)	1168 (46)	457 (18)	609 (24)
PWD 79	-	0-6-0ST	-	-	40 (25)	965 kPa (140 psi)	62.35 (14020)	1143 (45)	406 (16)	558 (22)
JAB 4	20N	0-6-0ST	(35T)	-	-	827 kPa (120 psi)	(12000)	1219 (48)	406 (16)	609 (24)
JAB 5	Mersey 1	0-6-4T	(68T)	-	-	1034 kPa (150 psi)	(26200)	1397 (55)	533 (21)	660 (26)